



GAS TOOL FASTENERS



(Pre-assembled, Single-Shot)

The fasteners are designed for use in Ramset Single-Shot Gas Tools (R150, T3SS)



SELECTION CHART

THREADED ROD HANGER		For suspended ceilings, piping and other items using 1/4" or 3/8" threaded rod. Fastener is pre-assembled to a 16 gage threaded rod hanger. 100 per jar.		
 	PART NUMBER	DESCRIPTION	R150	T3SS
	14TRHMP034	1/4" Rod hanger with 3/4" plated pin	■	■
	38TRHMP034	3/8" Rod hanger with 3/4" plated pin	■	■


Shank diameter = .104/.125
 Head diameter = .300

ONE HOLE STRAP		Used to attach conduit or armored cable to concrete. Fastener pre-assembled to a 16 gage conduit strap. 100 per jar, 3/8" 200 per jar.		
	PART NUMBER	DESCRIPTION	R150	T3SS
	38HSMP034*	3/8" Hole strap with 3/4" plated pin 	■	■
	12HSMP034	1/2" Hole strap with 3/4" plated pin	■	■
	34HSMP034	3/4" Hole strap with 3/4" plated pin	■	■
	10HSMP034	1" Hole strap with 3/4" plated pin	■	■

Shank diameter = .104/.125 *38HSMP034 = 18 gage, 200 per jar
 Head diameter = .300

CONDUIT CLAMP		Used to attach conduit to concrete. Pin pre-assembled to an 18 gage conduit strap. 1/2" 50 per jar and 3/4" 25 per jar.		
 	PART NUMBER	DESCRIPTION	R150	T3SS
	12CCMP034L	1/2" Conduit clamp with 3/4" plated pin	■	■
	34CCMP034L	3/4" Conduit clamp with 3/4" plated pin	■	■

Shank diameter = .104/.125
 Head diameter = .300

CEILING CLIP ASSEMBLY		Pre-assembled Ceiling Clip. Plated 14 gage clip. 100 per jar.		
	PART NUMBER	DESCRIPTION	R150	T3SS
	34CLIP	3/4" wide angle clip w/ 3/4" length pin	■	■


Shank diameter = .104/.125
 Head diameter = .300

SOLD IN CONVENIENT PLASTIC JARS




(Pre-assembled, Single-Shot)

SELECTION CHART


TIE STRAP HOLDER	Used to install temporary lighting and secure low voltage cable to concrete, uses a standard cable tie up to 3/8" in width. Fastener is pre-assembled to a 22 gage tie strap holder. 50 per jar.			
	PART NUMBER	DESCRIPTION	R150	T3SS
	TSHMP034	Tie strap holder with 3/4" plated pin	■	■

Shank diameter = .104/.125
Head diameter = .300

MECHANICAL PIN WITH WASHER	Used for the attachment of light gage metal to concrete and steel such as HVAC duct strap to concrete. Plated pin pre-assembled to a 1/2" domed washer. 200 per jar, 1" 100 per jar.			
	PART NUMBER	DESCRIPTION	R150	T3SS*
	M012	1/2" Plated step pin with dome washer	■	■
	M034	3/4" Plated pin with domed washer	■	■
	M034BB	3/4" Premium step pin with domed washer	■	■
	M100	1" Plated pin with domed washer	■	■


MUST USE WITH MAGNETIC WORK CONTACT ELEMENT (M150200)

Shank diameter = .125, Step Pin .104/.118
Head diameter = .300 (M012 = .250)
*Will fit R150 & T3SS with optional work contact element, P/N: M150200


1/4-20 THREADED STUD	Used to attach electrical components to concrete where removability of the component is required. Plated threaded stud. 200 per jar.				
	PART NUMBER	DESCRIPTION	SHANK LENGTH	R150	T3SS
	14STUD	1/2"	5/8"	■	■

NOT MADE IN USA

Shank diameter = .125

TOP HAT PIN	Used for general purpose fastening to concrete. Plated pin with top hat. 200 per jar.			
	PART NUMBER	DESCRIPTION	R150	T3SS
	MPO34TH	3/4" Plated pin with top hat	■	■

Shank diameter = .125
Head diameter = .300

BRIDLE RING	Pre-Assembled 2" Bridle Ring supports low voltage, data com, signal, and control cables 50 per box.		
	PART NUMBER	DESCRIPTION	T3SS
	BR2	2" Bridal ring	■

Shank diameter = .125